# **1977 CHEVROLET SUBURBAN**


1977 Chevrolet Suburban Series 10 and 20. Two-wheel and four-wheel-drive models.





# 1977 CHEVROLET SUBURBAN VALUE FEATURES

# **NEW FOR 1977**



New front end appearance features a redesigned grille • Headlamp bezels now dark gray metallic.


**Body side moldings** for Silverado and molding packages have new ochre paint trim.

**Rear speaker** is located in the right-hand rear trim panel.



New Exterior Decor Package features special two-tone paint treatment which uses the secondary color on the hood and between upper and lower body side moldings • Also includes color-coordinated hood stripes and a bright, stand-up-type hood emblem • See page 16 for color availability.

**Headliner** available separately or as part of Scottsdale and Silverado trim package, now Light Fawn.



**Door trim panels** now cover a greater area of the door.

**New seat trim** features new patterns and colors. See page 16 for more information.

**Engine lineup has been revised** to make the 6-cylinder engine standard on C10 Suburban. All V8 engines for this model are now available.

**New 305 V8** is the base engine on C20 Suburban and is available as an optional engine on C10 Suburban.

**Rear spring capacity** of the base K10 Suburban is reduced from 2250 to 2000 lbs. each.

**Heavy-duty front springs** for the K10-20 models now require heavy-duty front and rear shock absorbers • Capacity of the heavy-duty springs for K10-20 models is increased from 1900 to 2250 lbs. each.


**Delco Freedom Battery** now standard in all models.

# 1977 CHEVROLET SUBURBAN VALUE FEATURES NEW FOR 1977


**Wood-grain applique** used on interior trim has a new, simulated chestnut appearance.

**New paint colors** for both exterior and interior are highlighted on page 16.

New, improved ignition lock and retainer for theft protection plus new key combinations.



New wheel trim options are available for C-K10 models. A new full black and gray, stainless steel wheel cover in a spoked hub design is available • New optional white painted wheel features a spoke-type design.



## Other new options:

- · Color-keyed front floor mats
- Intermittent windshield wiper system
- Inside hood release latch
- 10-15B white-lettered tires for K10 Suburban

**Shock absorbers** • New optional 32mm shock absorbers available for 2-wheel-drive Suburbans

• Also available for 4-wheel-drive models in conjunction with heavy-duty front springs.


# 1977 CHEVROLET SUBURBAN MODELS





Suburban—page 4

# 1977 CHEVROLET SUBURBAN VALUE FEATURES




# Suburban does most anything a station wagon can, and many things a station wagon can't.

- More room than regular station wagons offer. Seats up to nine with available seating.
- Able to carry bigger loads (cargo and people) because under it all is a tough truck chassis.
- Over one-and-one-third times as much load space as most full-sized wagons. Approximately 93 cubic feet of inside luggage space when available third seat is not installed.

- Large glass area for good visibility.
- Four side doors for easy accessibility to passenger and cargo area.
- Two rear panel doors standard.
- Wagon-type tailgate available with manually retractable window glass.
- Electric tailgate window available.
- Low silhouette, contemporary styling make Suburban a versatile passenger /cargo carrying vehicle... an ideal travel wagon that's excellent for trailer towing.


# DIMENSIONS



# Glass Area (sq. in.)

| Windshield1447                 | Side rear window (each side). 1074 |
|--------------------------------|------------------------------------|
| Front side door including      | Rear:                              |
| ventipane (each side) 546      | ZW9 panel doors (total) 654        |
| Rear side door (each side) 488 | E55 tailgate1041                   |


# 1977 CHEVROLET SUBURBAN PASSENGER SEATING




**Seats up to nine facing forward** • Full-width front seat standard • Folding second seat available • And removable third seat is available with second seat.

**Suburban's load space** between back of third seat and tailgate is 35 cubic feet • With available third seat removed, there's 93 cubic feet of load space.


With second seat folded down and third seat removed, Suburban has 144 cubic feet of carrying capacity.




**Split design of second seat** lets either section fold independently for access to available third seat, or to handle long, narrow loads.



With both sections folded down, Suburban presents a large, flat, unobstructed load area.



Even with available third seat in place, Suburban has space left for cargo.



**Cargo barrier is provided** by Suburban's second seat in the folded position; it helps protect the lower front seat back from impact damage.

# 1977 CHEVROLET SUBURBAN TRAILER TOWING




**Series C20 Suburban** is rated for moving up to 14,500 pounds (Suburban, nine passengers, luggage and trailer) with Trailering Special package.

**Trailering Special** • Available only with V8 engine and Turbo Hydra-matic transmission • Includes heavy-duty Delco Freedom battery, power steering, GCW rating up to 14,500 lbs. (see chart).

| GCWR† IN POUNDS BY AXLE | RATIO | 6500   | 7000        | 7500         | 8000     | 8500     | 9000     | 9500             | 10,500     | 11,000      | 11,500   | 12,500    | 13,500 | 14,50         |
|-------------------------|-------|--------|-------------|--------------|----------|----------|----------|------------------|------------|-------------|----------|-----------|--------|---------------|
| TIRES, FRONT & REAR     | C-K10 |        |             |              |          |          |          |                  | L78-15B    |             |          |           |        |               |
| 1501 Date (1501)        | C-K20 |        | 1 1 2       |              | Mary .   |          |          |                  | 8.75-16.5C |             |          | 3.000     |        | 8.75          |
| ENGINE: 305-2 V8        | C-K10 | 3.07   | 3.40        | 3.73         | 4.11     |          |          |                  |            |             |          | 4 50 40   |        | 4.9           |
|                         | C-K20 |        |             |              | 4.10     |          |          |                  |            | 14.2        | 4.56     |           |        |               |
| 350-4 V8                | C-K10 |        | The Late of | and the same | 3.07     | 3.40*    |          | 3.73             | 4.11       | a Factorial |          | Feb 2014  |        | latin and the |
|                         | C-K20 | r Hall | 0.00        | Ubelia.      | 001      |          |          | 3.73             | 4.10       | IS NOT THE  |          | 4.56      |        |               |
| 400-4 V8                | K10   |        |             |              | or and a | 3.07     |          |                  | 3.73       |             | 4.11     |           |        |               |
|                         | K20   |        |             |              |          |          |          |                  | 11/6       | 12 344      | 4.10     |           |        | Pictor        |
| 454-4 V8                | C10   |        |             |              |          |          |          |                  |            | 3.07        |          | 3.40      | 3.73   |               |
|                         | C20   |        |             |              |          |          | - CA P   | Carrier Court of |            |             | 3.21     | 1,123,123 | 3.73   | 4.10          |
| TRANSMISSION            | ALL   |        | 4 4 1 1 24  | DE LE        | TURBO H  | HYDRA-MA | TIC (ALL | ENGINE           | S) OR 4-SF | PEED (305   | 350 V8 C | ONLY)     |        | 934           |

<sup>\*</sup>NOT AVAILABLE ON K MODELS. †GCWR. GROSS COMBINED WEIGHT OF VEHICLE, TRAILER, CARGO AND OCCUPANTS.

# 1977 CHEVROLET SUBURBAN ENGINE VALUE FEATURES



#### Standard 250 Six

The C10 Suburban offers Chevrolet's reliable Six that uses no-lead or regular fuel. Compression ratio is 8.0:1. Engine features 7 main bearings for durability, a 12-counterweight crankshaft and torsional dampeners for smoothness. Single-barrel carburetor is easy to service.

#### 400 V8


Available for Suburban K10-K20 models with 4-wheel drive. Uses no-lead or regular fuel.

#### 454 V8

Available for big loads and heavy towing on C10-20 models only. This high-torque 454 V8 with a 4-barrel carburetor operates on no-lead or regular grade gasoline. Camshaft is designed for added efficiency.

## **High Energy Ignition System**

Provides a spark up to 85% hotter compared with conventional systems. Solid state design eliminates points and ignition condenser. Higher voltages help fire worn spark plugs, ignite fuel charges leaner or richer than normal so suburban can go farther between scheduled tune-ups.



#### 350 V8

Available for higher all-around performance requirements, Suburban offers a 350 V8 with 4-barrel carburetor. It performs efficiently on no-lead or regular fuel.

#### **Full-Time 4-Wheel Drive**

All full-time 4-wheel-drive models in K10 and K20 Series come equipped with a V8 engine, Turbo Hydra-matic transmission and new transfer case warning light. With full-time 4-wheel drive you can move on or off the road without pausing to lock or unlock hubs or to shift from 2-wheel to 4-wheel drive. In fact front free-wheeling hubs are eliminated. A special interaxle differential compensates for variations between front and rear wheels. For special low-traction or unusual road surface situations, the interaxle differential may be locked out, permitting conventional 4-wheel-drive operation.

## **Conventional 4-Wheel Drive**

Suburban K10-K20 models with 3-speed or 4-speed manual transmissions are equipped with conventional 4-wheel drive. The two-speed transfer case has both high and low ranges for 4-wheel drive on unpaved surfaces, plus a high range in 2-wheel drive for highway travel. A power takeoff is provided for operating accessory equipment. Front free-wheeling hubs are standard.

# 1977 CHEVROLET SUBURBAN POWER TEAMS

| ENGINE | TRANSMISSION | TRANSFER CASE | R             | EAR AXLE |
|--------|--------------|---------------|---------------|----------|
| Type   | Type         | Make          | Make          | Ratio    |
| and    | and          | and           | and           | and      |
| Code   | Code         | Model         | Capacity (lb) | Code     |

|                    | 3.07<br>HE3                    | 3.40<br>HE4 | 3.73<br>GT4 | 4.11<br>H04 |        |        |        |
|--------------------|--------------------------------|-------------|-------------|-------------|--------|--------|--------|
| • 250 1-bbl L6—LD4 | 3-Speed Manual (Std)— M15      |             |             | _           | _      | X      | X(Std) |
| (Standard          | 4-Speed (Chevrolet CH465)— M20 |             |             | _           | X(Std) | X      | X      |
| Engine)            | Turbo Hydra-matic—M40          |             |             | _           | X(Std) | X      | X      |
| • 305 2-bb1 V8 LG9 | 3-Speed Manual (Std)—M15       |             |             | _           | _      | X(Std) | X      |
|                    | 4-Speed (Chevrolet CH465)—M20  |             | Chevrolet   | _           | X(Std) | X      | X      |
|                    | Turbo Hydra-matic—M40          |             | 3750 ♦      | _           | X(Std) | X      | X      |
| ■ 350 4-bbl V8—LS9 | 3-Speed Manual (Std)—M15       |             | ·           | _           | X(Std) | X      | _      |
|                    | 4-Speed (Chevrolet CH465)—M20  |             |             | X(Std)      | X      | X      | X      |
|                    | Turbo Hydra-matic—M40          |             |             | X(Std)      | X      | X      | X      |
| ■ 454 4-bbl V8—LF8 | Turbo Hydra-matic—M40          |             |             | X(Std)      | X      | X      | _      |

|   | C20 SERIES                             |  |   |                    |        |        | 4.10<br>GT5 | 4.56<br>HC4 |
|---|--|--|---|--------------------|--------|--------|-------------|-------------|
| • 305 2-bbl V8 LG9<br>(Standard Engine) | 4-Speed (Chevrolet CH465)<br>(Std)—M20 |  |   |                    | _      | _      | X(Std)      | ХЪ          |
|   | Turbo Hydra-matic—M40                  |  |   |                    | _      | _      | X(Std)      | Хb          |
| ■ 350 4-bbl V8—LS9                      | 4-Speed (Chevrolet CH465)<br>(Std)—M20 |  | _ | Chevrolet<br>5700♦ | _      | X(Std) | X           | Хb          |
|   | Turbo Hydra-matic—M40                  |  |   |                    | _      | X(Std) | X           | Хb          |
| ■ 454 4-bbl V8—LF8                      | Turbo Hydra-matic—M40                  |  |   |                    | X(Std) | X      | X           | _           |

|                    | 2.76<br>HC2                   | 3.07<br>HE3         | 3.73<br><b>GT4</b> | 4.11<br>HO4 |        |        |    |
|--------------------|-------------------------------|---------------------|--------------------|-------------|--------|--------|----|
| • 305 2-bb1 V8 LG9 |                               |                     |                    |             |        |        | X  |
| (Standard Engine)  | 4-Speed (Chevrolet CH465)—M20 | #205                |                    | _           | X(Std) | X      | X. |
|                    | Turbo Hydra-matic—M40         | New Process<br>#203 | Chevrolet          | _           | X(Std) | X      | x  |
| ■ 350 4-bbl V8—LS9 | 3-Speed Manual (Std)—MC1      | New Process         | 4000 ♦             | _           | _      | X(Std) | X  |
|                    | 4-Speed (Chevrolet CH465)—M20 | #205                | ·                  | X(Std)      | X      | X      | X  |
|                    | Turbo Hydra-matic—M40         | New Process         |                    | X(Std)      | X      | X      | X  |
| ■ 400 4-bbl V8—LF4 | Turbo Hydra-matic—M40         | #203                |                    | X(Std)      | Х      | X      | X  |

|                    | K20 SERIES                    |                     |                     |         |   |  |  |
|--------------------|-------------------------------|---------------------|---------------------|---------|---|--|--|
| • 305 2-bbl V8 LG9 | 3-Speed Manual (Std)—MC1      | New Process         |                     | X(Std)c | X |  |  |
|                    | 4-Speed (Chevrolet CH465)—M20 | #205                |                     | X(Std)  | Х |  |  |
|                    | Turbo Hydra-matic—M40         | New Process<br>#203 | Chevrolet<br>5700 ◆ | X(Std)  | X |  |  |
| ■ 350 4-bbl V8—LS9 | 3-Speed Manual (Std)—MC1      | New Process         |                     | X(Std)c | Х |  |  |
|                    | 4-Speed (Chevrolet CH465)—M20 | #205                | ·                   | X(Std)  | X |  |  |
|                    | Turbo Hydra-matic—M40         | New Process         |                     | X(Std)  | Х |  |  |
| ■ 400 4-bbl V8-LF4 | Turbo Hydra-matic—M40         | #203                |                     | X(Std)  | _ |  |  |

- Available for registration in the State of California when California Emission Certification is ordered.
- Not available for registration in the State of California.
- ♦ Locking Differential rear axle also available.

  a Locking Differential rear axle not available.

  b Locking Differential requires J55 HD Brakes.

  c Not available with J55 HD Brakes.


## **ENGINE RATINGS**

Engine ratings shown are not official at this time, and are for guide purposes only.

| SAE Net Ratings @ 85°F           | 250 1-bbl L6   | 305 2-bbl V8   | 350 4-bbl V8   | 400 4-bbl V8   | 454 4-bbl V8    |
|----------------------------------|----------------|----------------|----------------|----------------|-----------------|
| Net Horsepower Net Torque, lb-ft | 100 @ 3600 rpm | 140 @ 3800 rpm | 165 @ 3800 rpm | 175 @ 3600 rpm | †240 @ 3800 rpm |
|                                  | 175 @ 1800 rpm | 235 @ 2000 rpm | 255 @ 2800 rpm | 290 @ 2800 rpm | †370 @ 2800 rpm |

†For California only: Net Horsepower — 250 @ 3800 rpm Net Torque, lb-ft—385 @ 2800 rpm

# 1977 CHEVROLET SUBURBAN POPULAR OPTIONS




**Front and rear air conditioning available** or front only.

**Upper and lower body side moldings •** Not available with spear molding.

**Spear molding** • Bright with black insert to help protect body side finish.

Interior headliner • Included with Scottsdale or Silverado interior • Includes door-actuated dome lamp.

Full-length carpeting a separate option for Scottsdale Suburban with second seat • Includes rear wheelhousing carpeting • Helps tailor Suburban to customer needs.



**Comfortilt wheel** • Available only with Turbo Hydra-matic or 4-speed manual transmissions • Adjustable to any one of six driving positions.

**Cigarette lighter** • Automatic pop-out type • Included with Silverado or Scottsdale interiors.

**Bright metal wheel trim** • Depending upon model selection, bright hubcaps, Rally wheels, trim rings and wheel covers are available.

**Deluxe bumpers** • Heavy-gauge chromed steel with resilient impact strips • Available front and rear, all models.

Chromed bumpers • Heavy-gauge steel • Available front and rear for Custom Deluxe Suburbans

• Standard on Scottsdale, Silverado • Chromed front bumper guards with rubber impact strips also available separately with this option.


**Special instrumentation** • Includes voltmeter, oil pressure and water-temperature needle-type gauges.

**Simulated chestnut wood-grain instrument panel** • Available only with Z53 special instrumentation package • Included with Silverado interior.

Additional options • Power steering • Turbo
Hydra-matic • AM and AM/FM radios • New rearmounted speaker • Below Eyeline and camper-type
mirrors • Locking differential rear axle • Front
stabilizer (standard on 4-wheel-drive models) • Widebase tires • V8 engine oil cooler • Wheel covers
• Gauges • Speed and Cruise Control • Electric
clock • Soft-Ray tinted glass • Radial ply tires
• Electric tailgate window • Chromed grille • Dooredge guards • Cold climate package (Not available
with air conditioning. Includes 61-amp generator,
super heater and defroster, engine block heater and

anti-freeze protection to 40 degrees below zero).

# 1977 CHEVROLET SUBURBAN POPULAR OPTIONS



**Hubcaps—bright metal** • Bright with black paint trim • 5-spoke 10" design for Series 10 • 6-spoke 12" design for Series 20 • Center cut out for 4-wheel-drive models.

**Wheel trim rings—bright metal** • Requires bright metal hubcaps • Available for most Suburban models.




**Full wheel covers—bright metal** • Completely new design • Center cut out for 4-wheel-drive models.

15" Rally wheels • Includes bright center hubs and wheel trim rings • Available for most C-K10 models • Center hub cut out for 4-wheel-drive models.

**15"** styled wheels • White painted wheels with yellow and orange peripheral striping.

**Radial tires** • Available for most C-K10 models • LR78-15C radial ply whitewall tires are available for C-K10 models.



## Weight-Distributing Hitch Platform (also RPO)

- Required for trailers over 2,000 lbs.
- No-weld installation.
- Same holes in frame used for modified deadweight hitch.
- Capacity: 7,000 lbs.
- Ball hitch platform not included.

**Trailer wiring harness** • Heavy-duty 7-wire harness • Color-coded wires • Mounted to rear of frame • No rear connector included.

**Auxiliary battery** • 3,500-watt Delco Freedom battery • Front mounted under hood • Recommended for trailering.

**Engine oil cooler** • Supplements normal cooling through oil sump and engine block • Recommended for towing trailers of 2,000 lbs. capacity or greater • Requires V8 engine.

**Speed and cruise control** • Handy control button in direction signal lever knob adjusts to hold a steady speed • Provides driver comfort on long trips • Automatically disengages when brake pedal is applied • Requires V8 engine and automatic transmission.


Trailer hitch • Available in deadweight type.

# 1977 CHEVROLET SUBURBAN CUSTOM DELUXE TRIM LEVEL

"Custom Deluxe" base Suburban includes the following features and appointments:

#### Interior:

- Full-width color-keyed front seat upholstered in plaid pattern embossed vinyl.
- Color-keyed instrument panel pad.
- Speedometer dial indicates kilometers per hour as well as miles per hour.
- Molded door trim panels with integrated cushioned armrests.
- Tip-out ashtray and glovebox.
- Padded left and right sunshades.
- Front courtesy lamp.
- Black, full-length rubber floor mat.
- Vinyl-framed prismatic rearview mirror.
- Rear compartment coat hooks.



Special equipment bucket seats may be ordered in Blue or Buckskin vinyl trim. See the special equipment pages of the Truck Data Book.



- Bright upper and lower grille outline moldings, headlamp bezels and door handles.
- Bright right- and left-hand outside rearview mirrors, side door drip moldings.
- White-painted bumpers, hubcaps (except K models).
- Custom Deluxe fender nameplates.
- Suburban rear nameplate.

# 1977 CHEVROLET SUBURBAN SCOTTSDALE TRIM LEVEL

"Scottsdale" Suburban model includes the following features and appointments:

#### Interior:

All the items in the Custom Deluxe interior, plus the following additions or substitutions:

- Bright appearance items:
   Scottsdale nameplate on instrument panel pad, dome lamp trim, full front door sill scuff plates.
- Cigarette lighter.
- Dome lamps: Two, front and rear.
- Dome and courtesy lamp switches, door-activated.
- Floor mats, color-keyed.
- Full-length molded plastic headliner.
- Cowl and headliner insulation.
- Pillar trim panels.
- Plaid-patterned embossed vinyl seat upholstery.
- Full foam front seat cushion.
- Vinyl spare tire cover.



Special equipment bucket seats may be ordered in Blue or Buckskin vinyl trim. See the special equipment pages of the Truck Data Book.



#### **Exterior:**

All items on the Custom Deluxe interior, plus the following additions or substitutions:

- Scottsdale nameplates.
- Bright front and rear bumpers.
- Bright parking /turn signal lamp, side marker lamp and taillamp trim.
- Newly restyled bright hubcaps.
- Bright windshield reveal molding.
- Bright side rear window moldings.
- Additional horn.
- Spear-type black plastic body side upper molding with bright trim.


# 1977 CHEVROLET SUBURBAN SILVERADO TRIM LEVEL

"Silverado" Suburban model includes the following features and appointments:

## Interior:

All items in the Scottsdale interior, plus the following additions or substitutions:

- Choice of luxurious velour fabric and vinyl or grained vinyl seat upholstery.
- Cut-pile polyester carpeting, including rear compartment floor and wheelhousings with available second seat.
- Full-gauge instrumentation.
- New chestnut pattern wood-grain vinyl accents on instrument cluster, steering wheel (C10-20 only) and door trim panels.
- Storage pockets in front door trim panels with door closing assist straps.
- Secondary weatherstrips on side door.



Special equipment bucket seats may be ordered in Blue or Buckskin vinyl trim. See the special equipment pages of the Data Book.



- Bright upper body side and rear moldings.
- Silverado fender nameplates.
- Hood, and body-to-fender insulation.

# 1977 CHEVROLET SUBURBAN TWO-TONE EXTERIORS



New Exterior Decor package features special two-tone paint treatment which uses the secondary color on the hood and between upper and lower body side moldings • Also includes color-coordinated hood stripes and a bright, stand-up-type hood emblem • See page 16 for color availability.

#### **Suburban Estate**

Simulated wood-grain appliques between included bright upper and lower side and rear body moldings
• Redwood pattern and color • Includes Estate nameplates.





## **Special Two-Tone**

Secondary color applied between included bright upper and lower side and rear body moldings.

# 1977 CHEVROLET SUBURBAN EXTERIOR/INTERIOR COLORS

**Please Note:** Exterior and interior combinations shown in chart below are those *recommended* by Chevrolet; however, any exterior color combination may be ordered with any available interior color if the particular combination is desired by a customer.

| SEAT T                        | RIM         |             | М                | ODEL OPTI         | ON               | SEAT TRIM | COLOR AND O  | ORDERING CODE  |  |  |
|-------------------------------|-------------|-------------|------------------|-------------------|------------------|-----------|--------------|----------------|--|--|
| Fabric                        | . Cada      | M           | Custom<br>Deluxe | Scottsdale<br>Z62 | Silverado<br>YE9 | Blue      | Buckskin     | Red            |  |  |
|                               | ▲Code       |             |                  |                   | ILS              | VDD1      | VUU1         | VRR1           |  |  |
| Standard Vinyl                | W           | Bench       | X                | X                 | x                | XDD1      | XUU1         | XRR1           |  |  |
| Custom Vinyl                  | D           | Bench       |                  | X                 | X                | LDD1      | LUU1         | LRR1           |  |  |
| Custom Cloth                  |             | Bench       |                  |                   | condary          |           | DED INTERIOR |                |  |  |
| <b>♦EXTERIOR</b>              |             | )<br>       | Primar           | <u>y</u> 50       |                  |           | X X          | X X            |  |  |
| BLACK, MIDNIGH                | IT          |             | 86               |                   | 86<br>20         | X<br>X    | Α            |                |  |  |
| Blue, Lite                    |             |             | 86<br>86         |                   | 65               |           | X            | x              |  |  |
| Buckskin                      |             |             | 86               |                   | 60               |           | X            | X              |  |  |
| Tan, Santa Fe                 |             |             | 86               |                   | 12               | X         | X            | X              |  |  |
| White, Frost BLUE, LITE (Ligh | 4/          |             | 20               |                   | 20               | X         | A            |                |  |  |
| White, Frost                  | ι,          |             | 20               |                   | 12               | X         |              |                |  |  |
| BLUE, HAWAIIAN                | I (Modine   | <del></del> | 23               |                   | 23               | X         |              |                |  |  |
| Blue, Lite                    | · [meanur   | ••,         | 23               |                   | 20               | X         |              |                |  |  |
| White, Frost                  |             |             | 23               |                   | 12               | X         |              |                |  |  |
| BLUE, MARINER                 | (Dark) (N   | <u>f)</u>   | 25               |                   | 25               | X         |              |                |  |  |
| Blue, Lite                    | //          | -,          | 25               |                   | 20               | X         |              |                |  |  |
| White, Frost                  |             |             | 25               |                   | 12               | X         |              |                |  |  |
| BROWN, CORDOV                 | A (Dark)    | (M)         | 81               |                   | 81               |           | X            |                |  |  |
| Buckskin                      |             | ` '         | 81               |                   | 65               |           | X            |                |  |  |
| Tan, Santa Fe                 |             |             | 81               |                   | 60               |           | X            |                |  |  |
| White, Frost                  |             |             | 81               |                   | 12               | ,         | Х            |                |  |  |
| BUCKSKIN                      |             |             | 65               |                   | 65               |           | X            | X              |  |  |
| Mahogany                      |             |             | 65               |                   | 76               |           | X            | Х              |  |  |
| Tan, Santa Fe                 |             |             | 65               |                   | 60               |           | X            | X              |  |  |
| White, Frost                  |             |             | 65               |                   | 12               |           | X            | X              |  |  |
| GREEN, SEAMIST                | ' (Light) ( | M)          | 43               |                   | 43               |           | X            |                |  |  |
| White, Frost                  |             |             | 43               |                   | 12               |           | X            |                |  |  |
| MAHOGANY                      |             |             | 76               |                   | 76               |           | X            | X              |  |  |
| Tan, Santa Fe                 |             |             | 76               |                   | 60               |           | X            | Х              |  |  |
| White, Frost                  |             |             | 76               |                   | 12               |           | X            | Х              |  |  |
| RED, CARDINAL                 | (Medium     | )           | 70               |                   | 70               |           | X            | X              |  |  |
| Mahogany                      |             |             | 70               |                   | 76               |           | X            | Х              |  |  |
| Tan, Santa Fe                 |             |             | 70               |                   | 60               |           | X            | X              |  |  |
| White, Frost                  |             |             | 70               |                   | 12               |           | X            | X              |  |  |
| RED, METALLIC                 | (Dark) (M   | ()          | 71               |                   | 71               |           | X            | X              |  |  |
| Buckskin                      |             |             | 71               |                   | 65               |           | X            | X              |  |  |
| Mahogany                      |             |             | 71               |                   | 76               |           | X            | X              |  |  |
| Tan, Santa Fe                 |             |             | 71               |                   | 60               |           | X            | X              |  |  |
| White, Frost                  | TO (34)     |             | 71               |                   | 12               |           | X            |                |  |  |
| RUSSET METALL<br>Buckskin     | TC (MI)     |             | 68               |                   | 68<br>65         |           | X            | <b> </b>       |  |  |
|                               |             |             |                  |                   |                  |           | X            | <del> </del>   |  |  |
| Tan, Santa Fe<br>White, Frost |             |             | 68               |                   | 60<br>12         |           | X            | <del> </del>   |  |  |
| SILVER, SARATO                | GE /M       |             | 17               |                   | 17               | X         |              | <del>  x</del> |  |  |
| Mahogany                      | on (m)      |             | 17               | <del></del>       | 76               |           | х            | X              |  |  |
| White, Frost                  |             |             | 17               |                   | 12               | Х         |              | X              |  |  |
| TAN, SANTA FE                 |             |             | 60               |                   | 60               | A         | Х            | X              |  |  |
| Buckskin                      |             |             | 60               | <del>-</del>      | 65               |           | X            | X              |  |  |
| Mahogany                      |             |             | 60               |                   | 76               |           | X            | X              |  |  |
| White, Frost                  |             |             | 60               |                   | 12               |           | X            | X              |  |  |
| WHITE, FROST                  |             |             | 12               |                   | 12               | Х         | X            | X              |  |  |
| Blue, Lite                    |             |             | 12               | <u> </u>          | 20               | X         | X            |                |  |  |
| Buckskin                      |             |             | 12               |                   | 65               | X         | X            |                |  |  |
| Mahogany                      |             |             | 12               |                   | 76               |           | X            | Х              |  |  |
| YELLOW, COLON                 | IAL         |             | 53               |                   | 53               |           | Х            |                |  |  |
| Tan, Santa Fe                 |             |             | 53               |                   | 60               |           | Х            |                |  |  |
| White, Frost                  |             |             | 53               |                   | 12               |           | Х            |                |  |  |

<sup>♦</sup> Primary color shown in **BOLDFACE TYPE**; secondary colors shown in Lightface Type. (**M**): Metallic ▲ Seat Trim Codes: V—Plaid Pattern Vinyl; W—Buffalo Hide Vinyl; D—Striped Pattern Velour Cloth

# 1977 CHEVROLET SUBURBAN STANDARD VALUE FEATURES




### All this included at no extra cost:

- Massive grille design For efficient engine cooling.
- Power-Beam single headlamps—For night vision.
- Roof drip rails —Direct water away from door openings.
- Wraparound painted front bumpers Added fender protection.
- Amber bulb parking lamps—Clear vehicle identification.
- Full front wheelhousings—Greater front end protection.
- 12-point body mounting system For a smooth, quiet ride.
- Double-wall hood and fender construction Greater rigidity.
- Zinc-rich primer Sprayed on inner faces of both inner and outer front fender panels before assembly and final priming.
- Zinc coating—Baked on inner surfaces of side front door outer panels before forming and final priming.
- ELPO electrocoated primer For entire Suburban body with doors attached.
- Lexan® plastic taillamp lenses Virtually shatterproof.
- Dual 16" electric 2-speed wipers—Large wiped area.


- Dual-orifice windshield washer nozzles More efficient coverage.
- Flow-through power ventilation—Continuous inside air circulation.
- Large windshield glass area Excellent visibility.
- Adjustable front ventipanes Draft-free ventilation.
- Four side doors Easy entrance or exit.
- Keyless door locking—Easy vehicle locking.
- Two-key system For theft protection.
- Dual bright exterior mirrors, both sides Extra rear vision.
- Long 129.5" wheelbase Smooth, stable ride.
- 15 exterior paint colors Wide selection.
- Two-tone paint—Secondary colors in addition to Frost White available.
- Three interior trim colors—To suit customer preference.
- Fully padded instrument panel For safety and appearance.
- Front removable instrument cluster Easy to service.
- Seat-belt warning buzzer Switch located in driver's lap-belt retractor.
- Automatic locking seat-belt retractors—For outboard positions of first and second seats.

# 1977 CHEVROLET SUBURBAN CHASSIS VALUE FEATURES



## **Tough Truck Frame and Suspension**

Massive Girder Beam independent front suspension with coil springs on 2-wheel-drive models • Multileaf rear springs • Rubber-bushed spring eye shackles to reduce noise and ride harshness • Adding up to a smooth, easy, controlled ride.



## **Staggered Rear Shocks**

Positioned with one slanting forward, the other aft • Reduced brake and power hop.

### Salisbury Rear Axle

Large ring gear • Tapered roller bearings • Broad ratio coverage • Semi-floating on Series 10 models • Full-floating truck-type axle standard on Series 20 models, recommended for heavy trailer towing.

## **Finned Rear Brake Drums**

For efficient cooling • Outer edges formed to help exclude contaminants.

#### Front Disc Brakes Standard

Durable and self-adjusting • Resist fade, recover quickly from water immersion • Shielded for dust protection • Lining wear sensors on front disc brakes audibly signal when pads should be replaced.

### **Computer-Matched Brake Systems**

Matched to Gross Vehicle Weight.

# 1977 CHEVROLET SUBURBAN SPECIFICATIONS

| Series                       | C10                                   | C20                                    |  |  |  |  |
|------------------------------|---------------------------------------|--|--|--|--|--|
| Engine                       |                                       |  |  |  |  |  |
| Base Equip                   | 250 1-bbl. L6                         | 305 2-bbl. V8                          |  |  |  |  |
| Clutch                       | •                                     | 24 sq. in.                             |  |  |  |  |
| Air Filter                   |                                       |  |  |  |  |  |
| Oil Filter                   | , , , , , , , , , , , , , , , , , , , |  |  |  |  |  |
| Exhaust System               | 3 ,                                   |  |  |  |  |  |
| Emission Control Systems     | . Meet Government Requirements        |  |  |  |  |  |
| Suspension, Front            | Independent; Coil Springs             |  |  |  |  |  |
| Capacity                     |                                       | 3800 lb.                               |  |  |  |  |
| Springs @ Ground             | 1625 lb. ea.                          | 1750 lb. ea.                           |  |  |  |  |
| Shock Absorbers              | l" dia.                               | l" dia.                                |  |  |  |  |
| Suspension, Rear             | Salisbury Ax<br>Two-stage M           | le; Hypoid Drive;<br>ulti-leaf Springs |  |  |  |  |
| Axle Capacity                | 3750 lb.                              | 5700 lb.                               |  |  |  |  |
| Axle Ratio                   | 4.11                                  | 4.10                                   |  |  |  |  |
| Springs, Main @ Ground       | 2000 lb. ea.                          | 2000 lb. ea.                           |  |  |  |  |
| Shock Absorbers              | l" dia.                               | l" dia.                                |  |  |  |  |
| Brakes                       |                                       | Self-adjusting                         |  |  |  |  |
| Front                        | Disc; 11.86" Rotor                    | Disc; 12.5" Rotor                      |  |  |  |  |
| Rear                         | Drum; 11.15" x 2.75"                  | Drum; 11.15" x 2.75"                   |  |  |  |  |
| Booster                      | Dual Diaphragm                        | Dual Diaphragm                         |  |  |  |  |
| Parking                      | Cable to Rear Wheels                  |  |  |  |  |  |
| Electrical                   |                                       | gative Ground                          |  |  |  |  |
| Battery—Freedom Type         | 2500 watts @ 0°F.                     | 3200 watts @ 0°F.                      |  |  |  |  |
| Delcotron Generator          | 37                                    | amp.                                   |  |  |  |  |
| Frame                        |                                       | eel; 39,000 psi                        |  |  |  |  |
| Section Modulus              | 3.14                                  | 3.92                                   |  |  |  |  |
| Fuel Tank (nominal capacity) | 25                                    | 5 gal.                                 |  |  |  |  |
| Steering Gear Type           | Manual; Recirc                        | culating Ball Gear                     |  |  |  |  |
| Linkage                      | Paral                                 | lelogram                               |  |  |  |  |
| Transmission                 | Fully Synchronized<br>3-Speed         | 4-Speed CH465                          |  |  |  |  |
| Shift Location               | Steering Column                       | Floor                                  |  |  |  |  |
| Tires                        | (5) H78-15B (4PR)                     | (4) 8.75-16.5C (6PR)                   |  |  |  |  |
| Wheels                       | · (5) Disc<br>15" x 6"                | (5) Disc<br>16.5" x 6"                 |  |  |  |  |

# 1977 CHEVROLET SUBURBAN SPECIFICATIONS

| Series  | <b>K</b> 10  | K20  |  |  |  |
|---|--|--|--|--|--|
| Engine Base Equip. Clutch Air Filter Oil Filter Exhaust System Emission Control Systems |  |  |  |  |  |
| Suspension, Front Capacity Axle Ratio Springs @ Ground Shock Absorbers Stabilizer Bar   | Salisbury Axle; Hypoid Driv<br>3600 lb.<br>3.73<br>1850 lb. ea.<br>1" dia.<br>1.25" dia. | re; Single-stage 2-leaf Springs 3800 lb. 4.10 1850 lb. ea. 1" dia. 1.25" dia.  |  |  |  |
| Suspension, Rear Axle Capacity Axle Ratio Springs @ Ground Shock Absorbers              | Salisbury Axle; Hypoid Drive<br>4000 lb.<br>3.73<br>2000 lb. ea.<br>1" dia.              | e; Two-stage Multi-leaf Springs<br>5700 lb.<br>4.10<br>2800 lb. ea.<br>1" dia. |  |  |  |
| Brakes Front Rear Booster Parking   | Drum: 11.15" x 2.75"  Dual Diaphragm   |  |  |  |  |
| Electrical Battery—Freedom Type Delcotron Generator                                     | 3200 wo  | gative Ground<br>atts @ 0°F.<br>amp.   |  |  |  |
| Frame Section Modulus   | l .  | el; 39,000 psi<br>3.92   |  |  |  |
| Fuel Tank (nominal capacity)  | 25   | gal.   |  |  |  |
| Steering Gear Type Linkage  | · -  | ulating Ball Gear<br>entional  |  |  |  |
| Transmission Shift Location   |  | onized 3-Speed<br>g Column   |  |  |  |
| Transfer Case Shift Lever PTO Opening   | Single Lever   |  |  |  |  |
| Tires   | (5) H78-15B (4PR)  | (4) 8.75-16.5C (6PR)   |  |  |  |
| Wheels  |  |  |  |  |  |

# 1977 CHEVROLET SUBURBAN—GVWR SELECTOR

| GVW             | †GAWR | l (lbs) | Mini      | Minimum Equipment Required for GVW Rating |                   |  |  |  |  |  |
|-----------------|-------|---------|-----------|---|-------------------|--|--|--|--|--|
| Rating<br>(lbs) |       |         | Tire Capa | city (lbs ea)                             | A1 . T            |  |  |  |  |  |
| (IDS)           | Front | Rear    | Front     | Rear                                      | Chassis Equipment |  |  |  |  |  |

#### C10 SERIES

| ●=6050          | 3220 | 3220 | 1610 | 1610 | a  |
|-----------------|------|------|------|------|--|
| <b>♦ ■</b> 6400 | 3250 | 3440 | 1720 | 1720 | Standard   |
| ♦6800           | 3250 | 3750 | 1910 | 1910 | Center Seat (AT5) and Stabilizer<br>Bar (F59); or Center and<br>Rear Seats (AS3) |
| 7000            | 3400 | 3750 | 1910 | 1910 | Center and Rear Seats (AS3);<br>454 4-bbl V8 (LF8)                               |

### **K10 SERIES**

| <b>=</b> 6200 | 3220 | 3220 | 1610 | 1610 |          |
|---------------|------|------|------|------|----------|
| <b>=</b> 6800 | 3520 | 3520 | 1760 | 1760 | Standard |
| 7300          | 3600 | 3820 | 1910 | 1910 |          |

†GAWR's shown are the maximum for each axle with equipment listed. Other GAWR's are available, and they are determined as the minimum capacity of either axle, springs or tires.

# FRONT AND REAR TIRE AVAILABILITY CHART

### **C-K10 SERIES**

# Spare tire to match either front or rear tires must be ordered K10 models require matching front and rear tread

|          | FRO                             | NT      |              | REAR     |                                 |         |             |
|----------|---------------------------------|---------|--------------|----------|---------------------------------|---------|-------------|
| Capacity | Description                     | Option  | Number       | Capacity |                                 | Option  | Number      |
| (lbs ea) | Description                     | Highway | ▲On-Off Road | (lbs ea) | Description                     | Highway | On-Off Road |
|          |                                 |         | TUBE         | LESS     |                                 |         |             |
| 1610     | H78-15B                         | HL      | HR           | 1610     | H78-15B                         | HL      | HR          |
| 1610     | H78-15B<br>White Stripe         | нм      | _            | 1610     | H78-15B<br>White Stripe         | нм      | _           |
| 1760     | 10-15B                          | WR●     | _            | 1760     | 10-15B                          | WR●     |             |
| 1760     | 10-15B<br>White Stripe          | WS●     | _            | 1760     | 10-15B<br>White Stripe          | WS●     | _           |
| 1790     | L78-15B                         | LB      | LC           | 1790     | L78-15B                         | LB      | LC          |
| 1790     | L78-15B<br>White Stripe         | LD      | _            | 1790     | L78-15B<br>White Stripe         | LD      | _           |
| *1910    | L78-15D                         | LK      | _            | *1910    | L78-15D                         | LK      | _           |
| *1910    | L78-15D<br>White Stripe         | LL      | . —          | *1910    | L78-15D<br>White Stripe         | LL      | _           |
| 1910     | LR78–15C Radial<br>White Stripe | CD      |              | 1910     | LR78–15C Radial<br>White Stripe | CD      | _           |

#### **TUBE-TYPE**

| 1610 | 6.50-16C | MG | _  | 1610 | 6.50-16C | MG |    |
|------|----------|----|----|------|----------|----|----|
| 1720 | 7.00-15C | NH | -  | 1720 | 7.00-15C | NH | _  |
| 1800 | 7.00-16C | NK | NL | 1800 | 7.00-16C | NK | NL |

 $<sup>\</sup>Delta$ On-Off road front tires available on K10 models only.

Center and rear seats (AS3) not available.

<sup>●</sup>Available with standard 6 cyl. engine only

<sup>♦</sup>Requires V8 engine.

Available on K10 models only.

<sup>\*</sup>Rated 2030 capacity on K10 models.

# 1977 CHEVROLET SUBURBAN—GVWR SELECTOR

| GVW<br>Rating<br>(lbs) | †GAWR (lbs) |      | Minimum Equipment Required for GVW Rating |               |                     |  |  |
|------------------------|-------------|------|---|---------------|---------------------|--|--|
|                        | Front       |      | Tire Capa                                 | city (lbs ea) | Charle Familian and |  |  |
|                        |             | Rear | Front                                     | Rear          | Chassis Equipment   |  |  |

#### **C20 SERIES**

| 7100 | 3500 | 3980 | 1990 | 1990 | Standard   |
|------|------|------|------|------|--|
| 7500 | 3500 | 5200 | 2780 | 2780 | HD Rear Springs (G50);<br>HD Power Brakes (J55)                                    |
| 8200 | 3800 | 5560 | 2780 | 2780 | HD Front Springs (F60);<br>2850-lb ea Rear Springs (G51);<br>HD Power Brakes (J55) |

#### **K20 SERIES**

| 6800 | 3700 | 3980 | 1990 | 1990 | Standard              |
|------|------|------|------|------|-----------------------|
| 7500 | 3700 | 4700 | 1990 | 2350 | HD Power Brakes (J55) |
| 8400 | 3700 | 5500 | 2060 | 2750 | HD Fower Brakes (199) |

†GAWR's shown are the maximum for each axle with equipment listed. Other GAWR's are available, and they are determined as the minimum capacity of either axle, springs or tires.

## FRONT AND REAR TIRE AVAILABILITY CHART

#### C-K20 SERIES

Spare tire to match either front or rear tires is available at extra cost K20 models require matching front and rear tread

|                      | FRO         | DNT     |              | REAR     |             |               |             |
|----------------------|-------------|---------|--------------|----------|-------------|---------------|-------------|
| Capacity<br>(lbs ea) |             | Option  | ı Number     | Capacity |             | Option Number |             |
|                      | Description | Highway | ▲On-Off Road | (lbs ea) | Description | Highway       | On-Off Road |
|                      |             |         | TUBE         | LESS     |             |               |             |
|                      | T           |         |              | 1990     | 8.75-16.5C  | TR            | TB          |
| 1990                 | 8.75-16.5C  | TR      | TB           | 2350     | 8.75-16.5D  | TA            | TF          |
| 2350                 | 8.75-16.5D  | TA      | TF           | 2350     | 8.75-16.5D  | TA            | TF          |
| 2750                 | 10-16.5D    | _       | WF           | 2750     | 10-16.5D    | _             | WFe         |
| 2780                 | 9.50-16.5D  | UF      | UE           | 2780     | 9.50-16.5D  | UF            | UE          |
|                      |             |         | TUBE-        | TYPE     |             |               |             |
|                      | 1           |         |              | 2060     | 7.50-16C    | PB            | PC          |
| 2060                 | 7.50-16C    | PB      | PC           | 2440     | 7.50-16D    | PF            | PG          |
|                      |             |         |              | 2780     | 7.50-16E    | PK            | PL●         |
| 2440                 | 7.50-16D    | PF      | PG           | 2440     | 7.50-16D    | PF            | PG          |
| 2780                 | 7.50-16E    | PK      | PL           | 2780     | 7.50-16E    | PK            | PL          |

 $\Delta$ On-Off road front tires available on K20 models only.

Available on K20 models only.